

Corrpro Coke Breeze Data Sheet

Specialist Cathodic Protection Products for the Onshore Market

Coke Breeze Specification

Corrpro Companies Europe Ltd offer and hold a large stock and various types of coke breeze which is specialist to the Cathodic Protection Industry. Corrpro can supply coke breeze worldwide.

TECHNICAL DATA

Product	SP	DB	CS
Type	Metallurgical	Petroleum	Fine Grained Petroleum
Fixed Carbon %	85.50 max	98.20 min	98.50 min
Ash %	13.00 max	0.70 max	0.60 max
Volatiles %	1.50 max	0.60 max	0.60 max
Moisture	10.00 max	0.50 max	0.30 max
Size Grading	0-10mm 40% max <1.00mm 5% max >10.0mm	1-3mm 10% max <0.71mm 5% max >3.15mm	0-1mm 5% max >1.00mm
Bulk Density	700 – 850 Kg/m ³	750 – 900 Kg/m ³	850 – 1000 Kg/m ³
Resistivity	<0.5 ohm.cm	<0.15 ohm.cm	0.1 ohm.cm
Other		A surfactant can be added to assist in “deep bore hole” applications - DBW	A surfactant can be added to assist in “deep bore hole” applications - CSW

For a full stock list, description & availability please visit: www.corrpro.co.uk